1

Description

Use of services within a communication network with internet
mechanisms and an automation system

5

The invention relates to a system and a method for the use of
services within at least one communication network with inter-
net mechanisms and at least one automation system, as well as a
service access means for connecting an automation system to a
10 communication network.

The unpublished DE 1 022 98 79 describes a data processing sys-
tem with improved provision of services for the provision of
functionalities. The data processing system thereby has at
15 least one first service for activating and deactivating at
least one second service.

In a data processing system of this type services for the pro-
vision of functionalities can be implemented in particular as
20 so-called web services. Web service technology is used increas-
ingly in the internet and helps to transform the internet from
a user-centered information medium to an information and web
service environment that can be used directly by applications.
In this process standard internet technologies (HTTP, SOAP,
25 WSDL, UDDI) are generally used in order to be able to use web
services directly in an application.

The object of the invention is to improve the use of services
within a communication network with internet mechanisms and
30 within an automation system.

This object is achieved by a system with the features set out
in claim 1. A system is thereby proposed for the use of ser-
vices within at least one communication network with internet
35 mechanisms and at least one automation system, with components
of the automation system being coupled together by means of a
conventional field bus, with a service access means being pro-

vided to connect the conventional field bus to the communication network, with the service access means being provided as client for the services provided in the communication network, with the service access means having transformation means,

5   which are provided to adapt a first communication protocol of the services to a second communication protocol of the field bus.

This object is achieved by a method with the features set out
10 in claim 7. A method is proposed for the use of services within at least one communication network with internet mechanisms and at least one automation system with components coupled together by means of a conventional field bus, with which method a service access means connects the conventional field bus to the
15 communication network, the service access means operates as client for the services provided in the communication network and transformation means of the service access means adapt a first communication protocol of the services to a second communication protocol of the field bus.
20

This object is achieved by a service access means for connecting an automation system to a communication network with internet mechanisms, which is provided as client for services provided in the communication network and which has transformation
25 means, which are provided to adapt a first communication protocol of the services to a second communication protocol of a conventional field bus connecting components of the automation system.

30 Automation engineering systems generally have a complex structure. The components of the automation systems are networked by means of specific communication systems (e.g. actuator-sensor buses, field buses, industrial Ethernet). With the internet in particular there is a parallel standardized communication net-
35 work with internet mechanisms available worldwide, via which numerous services can be provided. According to the invention services are made available for automation engineering systems

in a flexible manner. These systems do not themselves necessar-
ily have to have an internet architecture with the correspond-
ing internet mechanisms or protocols. The flexible architecture
allows the transformation of services of the communication net-
5   work with internet mechanisms to the automation system with
lower-level conventional field bus beyond the boundaries of the
communication network with internet mechanisms. The invention
allows services to be commissioned for automation systems from
any location, thereby benefiting from the advantages of a
10   widely distributed network.

The service requested by the automation system ultimately be-
comes active in the automation system itself. This requires a
service access means to establish the connection between ser-
15   vices and automation system. According to an advantageous em-
bodiment of the invention this service access means is part of
the automation system, in other words it is integrated in the
automation system as a component of the automation system. This
reduces the number of components required in the system.
20

According to a further advantageous embodiment of the invention
the communication network has at least one central register
means to provide information about at least some of the ser-
vices. The service access means also has search means, which
25   can be used to address the central register means. There is
therefore an architecture, which is characterized in that there
are register means (Yellow Pages) in the communication network
with internet mechanisms, said means containing details of
available services. A service user does not necessarily have to
30   know these register means. An enquiry using the search means
takes said user to these register means where they obtain in-
formation about which services are available for their automa-
tion system. A service user can thereby be both a person (e.g.
customer, service engineer) or a technical system (e.g. unit,
35   computer, component).

4

In the internet in particular numerous services are provided as so-called web services. According to a further advantageous embodiment of the invention the services that are provided or used are such web services. Web services use standard internet
5 protocols and mechanisms, e.g. HTTP (HyperText Transfer Protocol), SOAP (Simple Object Access Protocol), WSDL (Web Service Description Language). The service user is directed to a first service provider via the selection (manual or automated) of the required web service. The first service provider will generally
10 require further resources (e.g. database server) to implement the service. Any number of further service providers are therefore called on to implement the service. The roles of service provider (= server) and service user (= client) therefore alternate within the components involved, without these mecha-
15 nisms, which are typical for the use of a web service, being visible to the actual service user. The service user is only concerned with their requested service and does not have to deal with details of implementation via web services. Combining flexible web services based on internet technologies with auto-
20 mation system engineering significantly extends the functionality of the automation system at its outer interface. In particular this allows flexible and location-independent access to automation systems, the provision of new services for automation systems and the automation of services or the autonomous
25 processing of services with or without manual initiation.

Automation systems can be coupled to different communication networks. According to a further advantageous embodiment of the invention the communication network is an intranet. Many dif-
30 ferent information-processing devices, for example PCs, laptops, mainframes, web servers, etc., can be connected to such an intranet. Some of these devices provide services, which can also be used by the components of the automation system. The different information-processing devices can have client or
35 server functionalities, with a combination of the two functionalities also being possible in one device.

The automation system or service access means can take on the
role of both client and server during the course of the ser-
vices, if according to a further advantageous embodiment of the
invention the service access means is also provided to provide
5   further services in the communication network.

The claimed method can advantageously be used to implement
software updates for the components of the automation system
via the internet, in particular to implement firmware updates.
10   This allows the component software to be loaded, updated or
supplemented in a user-friendly and largely automatic manner.

The invention is described in more detail below with reference
to the exemplary embodiments shown in the figures, in which:

15

    FIG 1   shows a system for the use of services within a com-
               munication network with internet mechanisms and an
               automation system,

20   FIG 2   shows a schematic diagram of a system for the use of
               web services in the internet by an automation system,

    FIG 3   shows a schematic diagram of a system for the use of
               a software update service by an automation system and

25

    FIG 4   shows the operational sequence of a software update
               service.

FIG 1 shows a system for the use of services 1, 2 within a com-
30   munication network 4 with internet mechanisms and an automation
system 5. The components 10 of the automation system 5 are cou-
pled together by means of a conventional field bus 8. A conven-
tional field bus 8 here is understood to be a field bus which '
is not provided for communication according to internet stan-
35   dard protocols. The conventional field bus 8 of the automation
system 5 is connected to the communication network 4 by means
of at least one service access means 6. The service access

means 6 is connected to the communication network 4 via a coupling 9. The service access means 6 is provided as client for the services 1, 2 provided in the communication network 4. The service access means 6 has transformation means 7, which are

5 provided to adapt a first communication protocol of the services 1, 2 to a second communication protocol of the field bus 8. The second communication protocol of the field bus 8 is thereby the communication protocol used by the components 10 connected to the field bus 8 to handle communication via the

10 field bus 8. The communication network 4 in the exemplary embodiment according to FIG 1 has a central register means 3 to provide information about at least some of the services 1, 2. The service access means 6 also has search means 15, which can be used to search and address the central register means 3 in

15 the communication network 4. The services 1, 2 and the central register means 3 can be provided using any information-providing means; in the exemplary embodiment they are provided using the computers 11, 12 and 13. The computers 11, 12, 13 are coupled together by means of connections 14 that are only shown

20 schematically here. The connections 14 can thereby be internet connections, which are provided by the interaction of a large number of widely distributed communication users and connections (not shown here). The service access means 6 in the exemplary embodiment is also used to provide further services 17 in

25 the communication network 4.

The transformation of services in the communication network 4 to services of automation systems 5 that can also be transmitted by means of the conventional field bus 8 is described in

30 more detail below. The service access means 6 essentially provides a gateway between the lower-level conventional field bus 8 and the communication network 4, e.g. the internet. In addition to access to the conventional field bus 8 the service access means 6 also has a connection to the communication network

35 4 (internet/intranet) and software components, which allow it on the one hand to provide services itself in the communication network (e.g. web services) and on the other hand to operate as

client for services/web services provided in the communication
network 4. Data or services reaching the service access means 6
via the latter route can be injected into the conventional
field bus 8 through the connection between the service access
5   means and said field bus, after they have been correspondingly
prepared by means of the transformation means 7 (e.g. protocol
adaptation, conversion to specific services of the field bus
system, previous continuing data processing, etc.). Depending
on the complexity of the data processing, the service access
10   means 6 can comprise just hardware or a combination of hardware
and software.

FIG 2 shows a schematic diagram of a system for the use of ser-
vices in the form of web services in the internet by an automa-
15   tion system. The automation system 21 is connected by means of
a conventional field bus 29 to a service access means 22. Ser-
vice providers 23, 24, 25, service users 26 and a central reg-
ister means 27 are coupled together by means of internet con-
nections 28 in an internet or intranet 20. A register means 27
20   is for example a platform-independent and programming-language-
independent directory service according to the UDDI (Universal
Description, Discovery and Integration) specification. The
principal architecture is independent of whether web service
components are present in the automation system 21 itself or
25   separate service access is provided.

The principle of service use with the aid of the system pro-
posed here is to be described in more detail below based on the
exemplary embodiment according to FIG 2. A service user in the
30   automation system, e.g. an automation component, wishing to use
a service in the internet or intranet 20, is directed to a
suitable service provider 23 via a suitable selection routine,
which operates with automatic or manual control. The service
provider 23 will generally require further resources (e.g. da-
35   tabase server) to implement the service. Any number of further
service providers 24, 25 are therefore called on to implement
the service. The roles of service provider and service user

therefore alternate within the components involved, without
these mechanisms, which are typical for the use of a web ser-
vice, being visible to the actual user in the automation system
21. The service user is only concerned with their requested
5   service and does not have to deal with details of implementa-
tion via web service mechanisms. The requested service must ul-
timately become active in the automation system 21. This is
brought about by the service access means 22, which establishes
the connection between web services and automation system 21.
10   This service access means 21 can either be a specific component
or part of the automation system. In the first instance it is
possible to use a web service in an existing automation system
(with specific communication mechanisms/protocols). In the sec-
ond instance the service access means 22 and/or a service pro-
15   vider 23 - 25 (e.g. a web server) is/are part of the automation
system. This reduces the number of components required in the
system as a whole, which then however have to be integrated in
the automation system.

20   FIG 3 shows a schematic diagram of a system for the use of a
software update service by an automation system 31. The automa-
tion system 31 is connected by means of a conventional field
bus 39 to a service access means 32. The service access means
32 is connected by means of internet connections 38 to a number
25   of service providers 33 - 36, central register means 37 and
service users 40, 41 in an internet 30. These internet users
each have the function of client 42 and/or server 43.

A system with the structure shown in FIG 3 allows services for
30   the automation system 31 to be commissioned from any location,
thereby benefiting from the advantages of a widely distributed
network, in the exemplary embodiment the internet 30. Automa-
tion systems 31 are generally coupled to different networks and
increasingly to a local intranet or even the internet 30. Many
35   different information-processing devices, for example PCs, lap-
tops, mainframes, web servers etc., are connected to or to-
gether in these networks. Some of these devices provide serv-

ers, which can also be used by automation devices. The location
of the service provider is thereby insignificant, as the inter-
net is worldwide. It is therefore evident that users of a cer-
tain service can be located anywhere and can use said service

5 for a specific (fixed) unit. The different information-
processing devices can have client or server functionalities,
with a combination of the two functionalities also being possi-
ble.

10 The use of the firmware update service is to be described with
reference to the example in FIG 3. A component of the automa-
tion system 31 connected to the field bus 39 in the automation
system 31 sends a request relating to a firmware update to the
internet 30 by means of the service access means 32. The auto-

15 mation component uses a central register 37 to find a service
provider 36, which provides the required firmware update as a
service. The service provider 36 in turn uses further service
providers 33 - 35, which in the exemplary embodiment supply the
required firmware. The operational sequence of such a firmware

20 update service is to be set out with reference to FIG 4.

FIG 4 shows an example of the operational sequence of a firm-
ware update web service. The respective communication steps be-
tween the communication partners involved in a communication

25 network are shown schematically. The communication partners
each have the functionality of server 53 and/or client 52. The
example of the operational sequence of a web service shows the
use of the web service by any service user 50, but in particu-
lar by a service access means 32 according to FIG 3, which sup-

30 plies this service to an automation component in an automation
system. The service user 50 at any location with a connection
to the communication network, in particular the internet, can
be a person at a computer or even an autonomously operating ma-
chine. The service user 50 wishes to use a firmware update web

35 service and either knows the address of a central register
means 57 or obtains this address using a search engine 55. In
the latter instance the service user 50 sends a search request

60 for a register means 57 to a search engine 55, which then transmits the results 61 found to the service user 50. The service user then connects to one of the identified register means 57, e.g. a register server, and as client sends a request 62

5 for a web service with the required functionality (in this instance a firmware update service) to the register means 57. In response 63 it receives from the central register means 57 an overview of possible service providers 56 and their addresses in the communication network and a brief description of the

10 services provided. In the next step the service user 50 selects one of the service providers 56 according to their specific requirements and connects to this server. The service user 50 as client sends a request 64 for a firmware update to the service provider 56, providing the latter with the necessary informa-

15 tion about where the required data is to be sent, e.g. an automation component in an automation system. The service user 50 thereby negotiates the details of service implementation (address of the module to be updated, details of the update) with the service provider 56. The service provider 56 confirms the

20 request of the service user 50 with an acknowledgment 65. In some instances the service provider 56 does not have all the data (e.g. firmware update files) necessary to implement the service it provides and must first obtain this from another web service. The procedure for this is similar: searching as an

25 autonomous client by means of a request 66 to a search engine 55 for a register means 57, e.g. a directory. The search engine 55 transmits the results 67 found to the service provider 56. The service provider 56 then uses a request 68 to request a suitable service (in this instance firmware holders) from the

30 register means 57 and as a result 69 obtains from the register means 57 the information where and how such a service is available. In the next step the service provider 56 as client uses a request 70 to request the necessary data from the firmware-holding server of the further service provider 54 found. The

35 further service provider 54 as server transmits the information 71 provided to the service provider 56. Once the service provider 56 has all the necessary data for the implementation of

the firmware update web service, it starts the provided service and informs the service user 50 via a message 72 of the status of web service processing.

5   In addition to the example of the use of a firmware update service described here, the described system and method can for example also be used for:
- diagnosis
- identification and maintenance functions
10 - process value display (snapshot)
- marketing of engineering services (sale of user software for automation units)
- loadable functions in automation devices
- teaching and practice tools
15

To summarize, the invention therefore relates to a system and a method for the use of services 1, 2 within at least one communication network 4 with internet mechanisms and at least one automation system 5, as well as a service access means 6 for
20 connecting an automation system 5 to a communication network 4. A system is proposed for the improved use of services 1, 2 within at least one communication network 4 with internet mechanisms and at least one automation system 5, with components 10 of the automation system 5 being coupled together by
25 means of a conventional field bus 8, with a service access means 6 being provided to connect the conventional field bus 8 to the communication network 4, with the service access means 6 being provided as client for the services 1, 2 provided in the communication network 4 and with the service access means 6
30 having transformation means 7, which are provided to adapt a first communication protocol of the services 1, 2 to a second communication protocol of the field bus 8.

A summary of web service technology is given below, to clarify
35 the invention further. This technology allows both direct communication between applications (the so-called services) and the setting up of applications from distributed components

(again services), i.e. loosely connected web services can work
together to complete a task. Web service technology uses stan-
dards such as XML and SOAP to scale from local communication to
communication via the intranet/internet. It is the basis for
5   distributed and integrated internet application, using existing
standards (e.g. W3C, IETF standards such as HTTP, XML, XML
Schema, XML Data Types, etc.) or new ones, together with W3C,
IETF defined standards such as SOAP, WSDL, UDDI. Web service
interfaces are described by meta-information (methods, parame-
10 ters (names and types)), generally in WSDL (Web Service De-
scription Language). This complete interface description is
adequate to call web services. It describes the end point
(port), at which the respective web service can be called and
is particularly useful for automatic communication with web
15 services. Web services are characterized by simple access, with
the boundaries between local APIs and web services ("web APIs")
blurring. Access is as simple as when generating and using a
local object. Web service technology is therefore the basis for
loosely coupled applications. It is characterized by message-
20 based communication and scalability due to statelessness. The
loose coupling (e.g. with SOAP) in particular has the advantage
of good compatibility in respect of changes in implementation
at client and server and reliable communication (port-based,
message-based, asynchronous). In message-based systems a client
25 packs messages into self-describing packets (messages) and
sends them in this form via the respective communication con-
nection. An agreement is only reached between sender and re-
cipient in respect of the message format used on the line. The
sole assumption is that the recipient understands the message.
30 No assumptions are made as to what happens after receipt of the
message or between sender and recipient. Standard web services
have the following characteristics: They can be accessed via a
communication network such as internet/intranet and have an XML
interface. Information about web services is stored in a regis-
35 try so that web services can be located using this. They commu-
nicate with the aid of XML messages via web protocols and sup-
port loosely coupled connections between systems.